AMENDMENTS TO THE CLAIMS

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims:

- 1. (Original) An absorbent article comprising a pouch filled at least in part with free-flowing cellulosic nits, the nits comprising papermaking fibers and a nit conditioner effective to improve free flow of the nits as compared to the nits without the nit conditioner.
- 2. (Original) The absorbent article of Claim 1, wherein the nit conditioner comprises a chemical additive selected from a debonder, a dispersant, a lubricant, and a surfactant.
- 3. (Original) The absorbent article of Claim 2, wherein the chemical additive is a debonder.
- 4. (Original) The absorbent article of Claim 3, wherein the debonder comprises a cationic polymer.
- 5. (Original) The absorbent article of Claim 2, wherein the chemical additive is hydrophilic.
- 6. (Original) The absorbent article of Claim 2, wherein the chemical additive is hydrophobic.
- 7. (Original) The absorbent article of Claim 1, wherein the nit conditioner comprises a silicone compound.
- 8. (Original) The absorbent article of Claim 7, wherein the silicone compound is amphoteric.

KCC-2134-CON 2 I/gdm

9. (Original) The absorbent article of Claim 1, wherein the nit conditioner comprises an oil or a wax.

- 10. (Original) The absorbent article of Claim 1, wherein the nit conditioner has a mass of about 0.1% or greater of the dry mass of the nits.
- 11. (Original) The absorbent article of Claim 1, wherein the nit conditioner comprises a surfactant selected from anionic and nonionic surfactants.
- 12. (Original) The absorbent article of Claim 1, wherein the nits have an AUL value of about 10 grams/gram or greater.
- 13. (Original) The absorbent article of Claim 1, wherein the nits have a Centrifuge Retention Capacity value of about 1.5 or greater.
- 14. (Original) The absorbent article of Claim 1, wherein the nits have an angle of repose of about 70° or less.
- 15. (Original) The absorbent article of Claim 1, wherein the nits comprise about 50% or greater by weight of eucalyptus fibers.
- 16. (Original) The absorbent article of Claim 1, wherein at least 90% by weight of the nits have a particle size range from 100 microns to 800 microns as determined by sieve analysis.
- 17. (Original) The absorbent article of Claim 1, wherein the nits have been prepared in a predetermined manner and wherein the nits have a substantially higher absorbent capacity than nits prepared in a manner identical to the predetermined manner but without the addition of the chemical additive, and wherein the chemical additive is substantially nonabsorbent.

KCC-2134-CON 3 I/gdm

18. (Original) The absorbent article of Claim 1, wherein the nits are substantially free of particles greater than 850 microns.

- 19. (Original) The absorbent article of Claim 1, further comprising superabsorbent particles within the pouch.
- 20. (Original) The absorbent article of Claim 1, wherein the pouch has a width of less than about 3 cm.
- 21. (Original) An absorbent article for use on the body of a wearer, the absorbent article having a longitudinal axis, a transverse axis, two longitudinal sides, a target zone and a body side, comprising:
 - a) a liquid impervious backsheet;
 - b) a liquid pervious topsheet attached to the backsheet;
- c) a conformable intake member comprising a pouch containing free-flowing particles;
 - d) an outer shaping member laterally surrounding the pouch; and
- e) a wicking barrier between at least a portion of the pouch and the outer shaping member.
- 22. (Original) The absorbent article of Claim 21, wherein the pouch has a width of less than about 5 cm and a length of about 10 cm or greater.
- 23. (Original) The absorbent article of Claim 21, wherein the free-flowing particles comprise hardwood nits.
- 24. (Original) The absorbent article of Claim 21, wherein the free-flowing particles comprise one of polymeric beads, hollow spheres, and mineral particles.

KCC-2134-CON 4 I/gdm

25. (Original) The absorbent article of Claim 21, wherein the free-flowing particles comprise at least about 30% nits by weight and no more than about 30% mineral matter by weight.

- 26. (Original) The absorbent article of Claim 21, wherein the free-flowing particles are substantially free of clay.
- 27. (Original) The absorbent article of Claim 21, wherein at least 25% by mass of the free-flowing particles have a particle size above 300 microns.
- 28. (Original) The absorbent article of Claim 21, wherein the free-flowing particles have a mean particle size between about 300 microns and about 600 microns.
- 29. (Original) The absorbent article of Claim 21, wherein the free-flowing particles have a Centrifuge Retention Capacity of about 1.5 g/g or greater.
 - 30. (Canceled)
- 31. (Original) The absorbent article of Claim 21, wherein the pouch further comprises an odor control agent.
- 32. (Original) The absorbent article of Claim 21, wherein the free-flowing particles further comprise one of an odor-control agent, an anti-microbial agent, and a surfactant.
- 33. (Original) The absorbent article of Claim 21, wherein the free-flowing particles further comprise an enzyme.
- 34. (Original) The absorbent article of Claim 21, further comprising superabsorbent particles within the pouch.

KCC-2134-CON 5 I/gdm

35. (Original) The absorbent article of Claim 21, wherein the free-flowing particles comprise cellulosic fibers and one of a debonder, a lubricant, a silicone compound, and a surfactant.

- 36. (Original) The absorbent article of Claim 21, wherein the free-flowing particles comprise cellulosic fibers treated with a quaternary amine debonder agent.
- 37. (Original) The absorbent article of Claim 21, wherein the free-flowing particles comprise cellulosic nits with added hydrophobic matter on at least a portion of the surface of the nits.
- 38. (Original) The absorbent article of Claim 21, wherein the free-flowing particles comprise cellulosic nits treated with 0.02% to 4% by weight of added hydrophobic matter.
- 39. (Original) The absorbent article of Claim 21, wherein the wicking barrier is a polymeric film.
- 40. (Original) An absorbent article for use on the body of a wearer, the absorbent article having a longitudinal axis, a transverse axis, two longitudinal sides, a target zone and a body side, the absorbent article comprising:
 - a) a liquid impervious backsheet;
 - b) a liquid pervious topsheet attached to the backsheet;
- c) a conformable intake member comprising a pouch containing free-flowing particles;
 - d) an outer shaping member laterally surrounding the pouch; and
- e) a wicking barrier between at least a portion of the pouch and the outer shaping member,

wherein the free-flowing particles have a Centrifuge Retention Capacity of about 1.5 g/g or greater.

KCC-2134-CON 6 I/gdm

41. (Original) An absorbent article for use on the body of a wearer, the absorbent article having a longitudinal axis, a transverse axis, two longitudinal sides, a target zone and a body side, the absorbent article comprising:

- a) a liquid impervious backsheet;
- b) a liquid pervious topsheet attached to the backsheet;
- c) a conformable intake member comprising a pouch containing free-flowing particles; and
- d) an outer shaping member laterally surrounding the pouch, wherein the free-flowing particles have a Flowability Coefficient of about 2 or greater.
- 42. (Original) The absorbent article of Claim 41, wherein the free-flowing particles also have a Centrifuge Retention Capacity of about 1.5 g/g or greater.
- 43. (Original) The absorbent article of Claim 41, wherein the pouch has a width of less than about 5 cm and a length of about 10 cm or greater.
- 44. (Original) The absorbent article of Claim 41, wherein the free-flowing particles comprise hardwood nits.
- 45. (Original) The absorbent article of Claim 41, wherein the free-flowing particles comprise one of polymeric beads, hollow spheres, and mineral particles.
- 46. (Original) The absorbent article of Claim 41, wherein the free-flowing particles comprise at least about 30% nits by weight and no more than about 30% mineral matter by weight.
- 47. (Original) The absorbent article of Claim 41, wherein the free-flowing particles are substantially free of clay.

KCC-2134-CON 7 I/gdm

48. (Original) The absorbent article of Claim 41, wherein at least 25% by mass of the free-flowing particles have a particle size above 300 microns.

49. (Original) The absorbent article of Claim 41, wherein the free-flowing particles have a mean particle size between about 300 microns and about 600 microns.

50. (Canceled)

- 51. (Original) The absorbent article of Claim 41, wherein the pouch further comprises an odor control agent.
- 52. (Original) The absorbent article of Claim 41, wherein the free-flowing particles further comprise one of an odor-control agent, an anti-microbial agent, and a surfactant.
- 53. (Original) The absorbent article of Claim 41, wherein the free-flowing particles further comprise an enzyme.
- 54. (Original) The absorbent article of Claim 41, further comprising superabsorbent particles within the pouch.
- 55. (Original) The absorbent article of Claim 41, wherein the free-flowing particles comprise cellulosic fibers and one of a debonder, a lubricant, a silicone compound, and a surfactant.
- 56. (Original) The absorbent article of Claim 41, wherein the free-flowing particles comprise cellulosic fibers treated with a quaternary amine debonder agent.

KCC-2134-CON 8 I/gdm

57. (Original) The absorbent article of Claim 41, wherein the free-flowing particles comprise cellulosic nits with added hydrophobic matter on at least a portion of the surface of the nits.

- 58. (Original) The absorbent article of Claim 41, wherein the free-flowing particles comprise cellulosic nits treated with 0.02% to 4% by weight of added hydrophobic matter, based on the total weight of the free-flowing particles and added hydrophobic matter.
 - 59. (Canceled)
- 60. (Previously Presented) The absorbent article of Claim 40, wherein the wicking barrier is a polymeric film.
- 61. (Previously Presented) The absorbent article of Claim 40, wherein the free-flowing particles comprise hardwood nits.